

The U-Tube: A Novel System for Sampling and Analyzing Multi-phase Borehole Fluid Samples during the Frio Brine Pilot Test

GCCC Digital Publication Series #05-04f

**B. M. Freifeld
R. C. Trautz
Y. K. Kharaka
T. J. Phelps
L. R. Myer
S. D. Hovorka
T. J. Collins**



Keywords:

U-Tube, Multiphase fluids, Geologic Sequestration- Brine

Cited as:

Freifeld, B.M., Trautz, R.C., Kharaka, Y.K., Phelps, T.J., Myer, L.R., Hovorka, S.D., and Collins, D.J., The U-tube: a novel system for sampling and analyzing multi-phase borehole fluid samples during the Frio Brine Pilot test: presented at the National Energy Technology Laboratory Fourth Annual Conference on Carbon Capture and Sequestration, Alexandria, Virginia, May 2-5, 2005. GCCC Digital Publication Series #05-04f, pp. 1-2.

The U-Tube: A Novel System for Sampling and Analyzing Multi-phase Borehole Fluid Samples during the Frio Brine Pilot Test

Barry M. Freifeld¹, Robert C. Trautz¹, Yousif K. Kharaka², Tommy J. Phelps³, Larry R. Myer¹, Susan D. Hovorka⁴, and Daniel J. Collins⁵

1. Lawrence Berkeley National Laboratory, Berkeley, CA 94720
2. U. S. Geological Survey, Menlo Park, CA 94035
3. Oak Ridge National Laboratory, Oak Ridge, TN 37830
4. Bureau of Economic Geology, University of Texas at Austin, Austin, TX 78713
5. Sandia Technologies LLC, Houston, TX, 77066

Abstract

A novel system has been deployed to sample and analyze multiphase fluids during a geologic CO₂ sequestration experiment conducted in the Frio brine aquifer in Liberty County, Texas. Project goals required high frequency recovery of representative and uncontaminated aliquots of a rapidly changing two-phase (supercritical CO₂-brine) fluid from 1.5 km depth. The data sets, collected using both the liquid and gas portions of the downhole samples, provide insights into the coupled hydro-geochemical issues affecting CO₂ sequestration in brine formations. The U-tube consists of a continuous loop of tubing open to the formation using a check valve. High purity compressed nitrogen is used to close the downhole check valve and drive the sample to the surface. The sample is collected at formation pressure, preventing degassing and contamination with outside gases, which would lead to rapid changes in sample chemistry. While the basic premise underlying the U-Tube sampler is not new, the system is unique because careful consideration was given to the processing of the recovered two-phase fluids. More specifically, strain gages mounted beneath the high-pressure surface sample cylinders measure the ratio of recovered brine to supercritical CO₂. A quadrupole mass spectrometer provided real-time gas analysis for perfluorocarbon and noble gas tracers that were injected along with the CO₂. The U-Tube successfully acquired frequent samples, allowing accurate delineation of the arrival of the CO₂ plume, and on-site analysis revealed rapid changes in geochemical conditions.

Presenting author: Robert Trautz rctrault@lbl.gov Voice: (510) 486-7954 Fax: (510) 486-5686

Lawrence Berkeley National Laboratory
MS 90-1116
One Cyclotron Rd
Berkeley, CA 94720

Larry Myer (same address) lrmeyer@lbl.gov Voice (510) 486-6456 Fax: (510) 486-5686
Barry Freifeld (same address) bmfreifeld@lbl.gov Voice (510) 486-4381 Fax: (510) 486-5686

Yousif Kharaka, Research Geochemist
U. S. Geological Survey, MS 427
345, Middlefield Road
Menlo Park, California 94025, USA
Phone: (650) 329-4535 Fax: (650) 329-4538 ykharaka@usgs.gov

Daniel J. Collins
Sandia Technologies, LLC.
140 Cypress Station Drive, Suite 130
Houston, TX 77090
Phone: (281) 586-5860 Fax: (281) 586-5870
Dan.Collins@sandiatech.com

Dr. Susan Hovorka
Bureau of Economic Geology
Jackson School of Geosciences
The University of Texas at Austin
Austin, TX 78713
phone (512) 471-4863, fax (512) 471-0140
susan.hovorka@beg.utexas.edu